





## **FEATURES**

- 4000kg (9,000 lbs) Capacity.
- Dual hydraulic cylinders, designed and made on high standard, high quality seals.
- 4 three-stage arms are suitable for more vehicle.
- Aero cable used for synchronization.
- Self-lubricating UHMW Polyethylene sliders and bronze bush.
- Exclusive feature: single-point safety release by handle.
- Stackable rubber pad with 1.5" and 2.5" extension adaptors.
- Automatic arms restraints.
- Hydraulic power unit.





## **COMPACT LINE OF TWO POST LIFTS**

PEAK compact line model 208C are made on PEAK high quality manufacturing standard with some advanced features like three-stages arms, single-point safety release, etc,but with competitive price!



## **EXCLUSIVE FEATURE!**

Single Point Lock Release Lever. This Lever Release Locking Mechanisms In Both Columns From One Column.



The stackable rubber pad assembly with 1.5" \ 2.5" extension adapters.



4 three-stages arms are suitable for more vehicles. Extremely high carriages, automatic arms restraints, protect rubber door guards, self-lubricated sliders... make PEAK compact line of two post lifts with many advanced features and high quality.



Optional 24V LED lights for Floor plate 2-post lifts: Kits 20101. plus extension cable 20103.

## **SPECIFICATIONS**

Model		Lifting Capacity	Lifting Time	Α	В	С	D	Е	F	Gross Weight	Motor
	el Style			Lifting Height	Overall Height	Overall Width	Drive-Thru Clearance	Width Between Columns	Minimum Pad Height		
208	C Clearfloor Chain-drived	4.0T (9,000 lbs.)	45 Seconds	1815-1917mm (71 1/2" - 75 1/2")	3602mm (141 3/4")	3390mm (133 1/2")	2554mm (100 1/2")	2780mm (109 1/2")	90mm (3 1/2")	636kg (1,402lbs)	3.0HP