# MODEL 430 430E Non-Alignment Four-post Lift


# MODEL **430 430E** Non-Alignment Four-post Lift


As another line of PEAK family, our four post lifts share the same name of quality, longevity, safety and with more flexible option.



#### FEATURES

- Air-released safety lock for convenient operation and reliability.
- Mechanical self-locking device and cable-breaking protection.
- Aircraft quality synchronization cable.
- Skid proof diamond platform.
- Hydraulic cylinders are designed to high standards using high quality seals.
- Strict quality control of cylinders with flow restrictors to keep a constant speed.







### EXCLUSIVE FEATURE !

Electric control device With UP, LOCK and DOWN buttons

With C.E. stop switch at 300 mm from ground and alarm tone when lowering down from 300 mm to ground make the lift more safety.



Oil-water separator and Solenoid air valve are installed on the power side column.



**Optional Air Line Kits** All peak four post lifts are designed to use the air line kits for rolling jack. Kits No.:40106




**Optional Rolling Jacks** RJ-20A pneumatic hydraulic type 9.0T

#### SPECIFICATIONS


Model	Lifting Capacity	Lifting Time	А	В	С	D	Е	F	G	Н	l I	J	K		Motor Power
				Overall Length (No Inc.Ramps)		Width Between Posts	Max. Lifting Height	Overall Height	Minmum Height	Max. Underneath Height	Drive-Thru Clearance	Width Between Runways	Outside Edge of Runways		
430	13.5T (30,000lbs)	116S	7800mm (307")	6514mm (256 1/2")	3794mm (149 3/8")	3348mm (131 3/4")		2332mm (91 7/8")	265mm (10 1/2")	1674mm (65 7/8")	2992mm (117 3/4")	1390mm (54 3/4")	2610mm (102 3/4")	2442kg (5,384lbs)	4. 0HP
430E	13.5T (30, 000lbs)	116S	9300mm (366 1/8")	8014mm (315 1/2")	3794mm (149 3/8")			2332mm (91 7/8")	265mm (10 1/2")	1674mm (65 7/8")	2992mm (117 3/4")	1390mm (54 3/4")	2610mm (102 3/4")	3098kg (6,830lbs)	4. 0HP







Electrical hydraulic power systemc, abled-rived.



Optional platform extension kits add an extra 737mm(29") length to the platform.

Kits No.:43001(430)



Optional LED lighting: 24V LED light. Kits No.:40104