
PEÅK<sub>®Lift</sub>

The MC-600P has same steel structure as the MC-600, but adopt pneumatic hydraulic pump as the power supply in stead of electricity.



## **FEATURES**

- Pneumatic hydraulic pump control
- Manual release safety lock with auto activation
- Skid proof diamond platform
- Removable rear coocenvenient for rear wheel changing.
- Quick install and dismount approach ramps
- Adjustable wheel vise installing to extend axle base up to 410mm(16 1/8")
- Wheel vise design imitate the tire cure shape with screw adjustment
- Standard tool tray













Rear Tire removal cover removable platform cover plate is convenient for rear wheel changing.



Optional length extension kit adds an extra 400mm length on the platform for the long axle vehicle.

Kits No.: MC002



Optional Width extension kit adds an extra width of 600mm on the platform to be suitable for three or four-wheel motorcycles.

Kits No.: MC001



Optional vehicle securing belt tightens the vehicle before lifting.

Kits No.: MC006



Optional lifting jack lifting capacity: 500kg. Perfect for wheel removal.

Kits No.: MC005

## **SPECIFICATIONS**

Model	Style	Lifting Capacity	Lifting Time	А		В	С	D		
				Lifting Height	MinimumPad Height	OverallLength (Inc.Ramp)	Runway Length	Overall Width	Gross Weight	Air pressure range
MC-600P	Motorcycle	600kg	23Seconds	155-1090mm (61/8"-43")	155mm (6 1/8")	2700mm (106 1/4")	2250mm (88 5/2")	750mm (29 1/2")	228kg (503lbs)	0.6MPa